

Waddell Recessed Product Specifications

Statement of Line:

- 1400 Series - Recessed Case, 1/4" Tempered Glass Minimally Framed Bypass Doors
- 1600 Series - Recessed Case, 3/16" Tempered Glass Fully Framed Bypass Doors (shown)

Materials:

- 6063-T5 Aluminum Extrusions
- 3/4" Plywood Box Construction
- 2-5/16" Capping Metal with Integral Bypass Door Track
- Tempered Glass Doors and Shelves

Options:

Locks (Keyed Alike)

- Ratchet Locks (Shown)
- Plunger Locks

Frame Color:

- Clear Satin Anodized (Standard/Shown)
- Black Powder coat
- Specialty Powder coat (Color Match)

Lighting

- 120V LED Tube Light (4000K)
- 120V 4" Round LED Recessed Lighting (Adjustable - 3000K/4000K/5000K)

Shelving (2, 3, or 4 tiers, 1 Set Behind Each Door, 25 lb. Standard Weight Limit per Shelf):

- KV Standards and Brackets (1/4" or 3/8" Tempered Glass Available)
 - 20" MAX DEPTH
- Hanging Shelves and Cable System (3/8" Tempered Glass) (shown)

Box Surfaces:

- Natural Cork
- High Pressure Laminate
- Wood Stain Finish (Birch)
- Tackable Fabric (FR701, Tier 1, Tier 2)
- PremaTak Vinyl
- Forbo Cork
- Special Material (Subject to Testing)

Rough Opening Sizing:

- Maximum Opening Size without Oversize Surcharge: 49.5" H x 149.25" W x 15.5" D
 - RO over this Width will be split and built in 2 sections.
- Box Height and Width Sizing: 1" Overall Smaller than Rough Opening
- Box Depth Sizing: 1/2" Smaller than Rough Opening
- Maximum Opening Height for 1/4" Tempered Glass Minimally Framed Sliding Doors: 73" (1400)
- Maximum Opening Height for 3/16" Tempered Glass Fully Framed Sliding Doors: 87" (1600)
- Maximum Opening Depth: 47"
- If Opening Width over 22 Feet, Must Review with Engineering Team
- Standard is not providing any trim or finishing materials for opening.

