

## 900DC Product Specifications

### Statement of Line:

- 900DC-MF, Fully Recessed Case, 1/4" Tempered Glass Minimally Framed Sliding Doors
- 900DC-FF, Fully Recessed Case, 3/16" Tempered Glass Fully Framed Sliding Doors
- 900DC-PVT, Fully Recessed Case, 2.5" Profile, 3/8" Tempered Glass Pivoting Doors (shown)

### Materials:

- 6063-T5 Aluminum Extrusions
- 3/4" Plywood Box Construction
- 1.5" Face Fully Recessed Tube Frame (2" Deep Tube Frame)
- Tempered Glass Doors and Shelves

### Options:

#### Locks (Keyed Alike)

- Ratchet Locks
- Plunger Locks
- Cylinder Locks (Only Option for Pivoting Doors)

#### Frame Color:

- Clear Satin Anodized (Standard/Shown)
- Black Powder coat
- Specialty Powder coat (Color Match)

#### Lighting

- 120V LED Tube Light (4000K)
- 120V 4" Round LED Recessed Lighting (Adjustable - 3000K/4000K/5000K)
- Light Shield Available

#### Shelving (2, 3, or 4 tiers, 1 Set Behind Each Door, 25 lb. Standard Weight Limit per Shelf):

- KV Standards and Brackets (1/4" or 3/8" Tempered Glass Available)
  - 20" MAX DEPTH
- Hanging Shelves and Cable System (3/8" Tempered Glass) (shown)

#### Box Surfaces:

- Natural Cork
- High Pressure Laminate
- Wood Stain Finish on Birch Veneer
- Tackable Fabric (FR701, Tier 1, Tier 2)
- PremaTak Vinyl
- Forbo Cork
- Special Material (Subject to Testing)

### Rough Opening Sizing:

- Maximum Size without Oversize Surcharge: 50.5" H x 151" W x 17.5" D
  - RO over this Width will be split and built in 2 or more sections.
- Frame Height and Width Sizing: 1" Overall Smaller than Rough Opening
- Depth Sizing: RO Depth - .5" (Gap) - 2" (Frame Depth) = Box Depth (Frame Sits Flush with RO)
- Maximum Opening Height for 1/4" Tempered Glass Minimally Framed Sliding Doors: 74" (900DC-MF)
- Maximum Opening Height for 3/16" Tempered Glass Fully Framed Sliding Doors: 88" (900DC-FF)
- Maximum Opening Height for 3/8" Tempered Glass Pivoting Doors: 97" (900DC-PVT)
  - Cases over 96" tall must be reviewed by Engineering to Confirm Shipping Configuration and Case Breaks
- Maximum Opening Depth: 50"
- If Opening Width over 22 Feet, Must Review with Engineering Team
- Standard is not providing any trim or finishing materials for opening.

